



## 3034D

### Create Precise Seam Finishes

### Overview

Give a professional look to your next project with serged seam finishes. Seams lie flatter and look better with an overlock stitch. Home décor projects often suggest the use of a serger for rolled hems, secure seams and differential feed. Choose from a 3 or 4 thread look and enjoy the new and easy threading method. The 3034D features two needles and 3 / 4 thread with differential feed. Create stitches from 2.0 to 4.0 mm in length. The differential feed ratio of 0.7 – 2.0 gives improved stitch quality and the free arm makes it easier to sew sleeves, trouser legs and other hard to reach places.

### Features

#### Basic Features

Lighting	Normal Light
Needle Threading System	No
Thread Tension	Manual (Upper Dial Type)
Adjustment for Thread Tightness	No
Electronic Speed Control	No

#### Sewing Features

Maximum Sewing Speed (Stitches Per Minute)	1,300
Feed Dog	Differential feed
Built-in Sewing Stitches (Includes Buttonhole Styles)	3 / 4 thread overlock, blind hem, rolled hem
Stitch Width	3.0 - 7.0mm
Stitch Length	0.8 - 4.0mm
Presser Foot Pressure Adjustment	Yes
Free Arm	Yes
Table	No
Specialty Feet Included	Yes (Additional specialty feet may be available. See Optional Accessories)

#### Carton Contents

Accessory Storage	Yes
Included Accessory Feet	Blind stitch foot, gathering foot

<b>Table</b>	No
<b>Other Included Accessories</b>	Soft cover, accessory bag with trim trap, spool nets (4), spool caps (4), needle set, cleaning brush, hexagonal driver, tweezers, instructional DVD and operation manual
<b>Foot Controller</b>	Yes

## Other

<b>Warranty</b>	1/5/25 year serger warranty. See serger warranty for details.
<b>UPC Code</b>	012502616535
<b>Machine Dimensions (H x W x D)</b>	13.4" x 11.96" x 11.16"
<b>Machine Weight</b>	12 lbs
<b>Shipping Weight</b>	16 lbs
<b>UL/CSA Listed</b>	Yes, 110v

## Serger Features

<b>Overlock Seam Width</b>	3.0 - 7.0
<b>Double Chain Stitch</b>	No
<b>Cover Stitch</b>	No
<b>2/3 Thread Change</b>	No
<b>Differential Feed</b>	0.7 - 2.0mm
<b>Change for Rolled Hemming</b>	Removable
<b>Underlooper Threader</b>	Yes
<b>Stitch Fingers</b>	1
<b>Knife Drive Type</b>	Down side

## Multi-Needle

<b>Threads</b>	3 / 4
<b>Number of Needles</b>	2
<b>Color-Coded Thread System</b>	Yes